

Display setup M1 / M2 meeting rooms

There are 3 options to connect your device to the displays in the M1 and M2 meeting rooms of Parc51:

1. **Connect only to the display of the M1 meeting room**
2. **Connect only to the display of the M2 meeting room**
3. **Mirror the display from the M1 to the M2 meeting room**

The setup for each option is explained below.

To keep the setup working as intended, please **don't disconnect** or replace any cables from the displays or the devices in the tables.

Connect only to the display of the M1-meeting room

1. Connect the USB C connector on the table in M1-Meeting room to your device.
2. Turn on the display in M1-Meeting room
3. Set the source of the display to **HDMI 2** with the display remote:



4. Make sure your device output is set to external devices
5. Make sure the HDMI switch **in the table in M2-Meeting Room** to “2” using the button on the switch:



6. Connecting the Logitech **meeting camera**
 - a. Normally by connecting the USB-C cable to your device this should activate the meeting room camera and microphone (on the camera and on the table) to your device

Connect only to the display of the M2-meeting room

1. Connect the USB-C cable on the table in M2-Meeting room to your device.
2. Turn on the display in M2-Meeting room
3. Set the source of the display to **HDMI 2** with the display remote:



4. Set the HDMI switch in the table in M2-Meeting Room to “1” using the button on the switch :



5. Make sure your device in M2-Meeting room is set to external devices
6. Connecting the meeting camera in M2-Meeting room
 - a. Also connect the USB-C cable to your device located in M2-Meeting room

Mirror the display from the M1 to the M2 meeting room

1. Connect the USB-C cable on the table in M1-Meeting room to your device
2. Turn on the display in M1-Meeting room and M2-Meeting room
3. Set the source of the displays in M1 **and** M2 to **HDMI2**



4. Set the switch in the table of M2-Meeting room to “2” using the button on the switch:



5. Make sure your device output is set to external devices
6. Connecting the **Logitech meeting camera**
 - a. Normally by connecting the USB-C cable to your device this should activate the meeting room camera and microphone (on the camera and on the table) to your device